



Liquid Colorants for Tinting Cementitious Bagged Goods

LIQUID COLORANTS

DESCRIPTION AND USE:

Multicoat's Liquid Colorant Jars are 4 ounce, pre-measured, liquid colorant tint, used to color select bags (50-lbs or 65-lbs) of polymer modified cementitious coatings to various colors. Ideally suited for Multicoat's Micro-Topping, Overlay Stamp Mix, Top Kote, and Krete Kote systems. Can also be used with other bagged cementitious products.

ADVANTAGES:

- *Single Component Packaging*
- *Easily Disbursed in Water*
- *Eliminates Measuring*
- *Low Cost*
- *Environmentally Friendly*
- *Consistent Colors*

BASIC USE:

Liquid Colorant Jars are used to tint cement based dry materials such as bags of Multicoat's Micro-Topping, Overlay Stamp Mix, Top Coat, and Krete Kote to different colors. The Liquid Colorant Jars are poured into with the mixing water before adding the dry powder material. No measuring is required.

COLOR:

Lite Grey, Sagestone, Clay Brick, Sand, and Taupe

PACKAGING:

Packaged in 4 ounce containers, 12 containers per case.

USAGE:

Multiple jars may be used to achieve the desired degree of color. Maximum of 3 jars per 65-lb bag.

SURFACE PREPARTION:

Follow the appropriate application instructions for system or products being installed.



Liquid Colorant Jars



Colorant Added to Water



MIXING:

Measure clean water to be mixed with bagged material. Start with a clean mixing container, add water. Thoroughly shake each jar prior to opening. Pour in the number of 4 ounce jars desired. Then mix with mechanical mixer until thoroughly dissolved. While stirring, slowly add dry bagged goods into colored water. Multicoat used the formula of 2-gallons of water per 65-lb bag of dry material when the color charts were generated.

APPLICATION:

Follow application instruction for material (system) being applied. All Krete Kote, or Multi-Stamp Mix applications must be sealed with either Multicoat's Acrathane Colorseal or Multicoat's Clear Sealer.

COLOR:

When using the Liquid Colorant, the final color of the finished project can be affected by several factors; workmanship of the placed material, thickness of the material, weather conditions, substrate absorption, amount of water used, amount of dry material used, mixing, etc. It is understood that there is the possibility of color variations in the final finished appearance.

LIMITATIONS:

Do not apply if precipitation is expected with twelve hours of application. Do not apply if ambient air temperature is 40° F and falling or above 100° F and rising. Do not add other materials to the mixture of the product.

STORAGE:

Store jars in a cool, dry location. Store away from direct contact with the ground or concrete. Protect from weather and other possible damage. Shelf life is approximately 18 months in unopened jars.

CLEANING:

Clean with warm soapy water immediately after use. Once dried, material will require mechanical means for removal.

WARRANTY DISCLAIMER:

There are no warranties which extend beyond the description of the fact hereof. Seller expressly disclaims all other warranties regarding the use of its products, whether expressed or implied, including the implied warranties of merchantability and for fitness of a particular purpose. Since use of the product is beyond the Seller's control, the Buyer assumes all risk of use. **EXCLUSIVE REMEDY:** Seller's sole obligation, and buyer's exclusive remedy shall be to replace material if found to be defective. **DAMAGE LIMITATION:** Seller shall not be liable for any damages, injury, loss, direct or consequential, resulting from its products. The parties intend that the limitation of damages, including consequential damages, applies even if the exclusive remedy provided for herein fails of its essential purpose. **FOR PROFESSIONAL USE ONLY:** Multicoat products should be used by licensed contractors. Multicoat is not a contractor and the contractor remains liable for all damages and inadequate product performance caused by construction means, methods, sequences and techniques that are used to install the product which may include: design and construction of the substrate and the selection and installation of all sealants, flashings, and related components.



MULTICOAT® CORPORATION

West Coast

Toll Free: (877) 685-8426

(949) 888-7100 Fax (949) 888-2555

Website: www.multicoat.com

E-mail: info@multicoat.com

MULTICOAT® PRODUCTS, INC.

East Coast

Toll Free: (800) 660-6729

(304) 586-0616 Fax (304) 586-0620

Website: www.multicoat.com

E-mail: info@multicoat.com

AVAILABLE THROUGH

The Coating of the Future... Today

MC413
LC