



A Water Based Decorative Concrete Stain

MULTI-STAIN

DESCRIPTION & USE

Multicoat's MULTI-STAIN is a water based stain designed to be applied to a variety of Multicoat's Systems. It can also be applied on most cementitious substrates such as pool decks, driveways, walkways, masonry walls, stucco, pre-cast concrete, etc. MULTI-STAIN is an acrylic based concrete stain furnished in factory blended containers. It is used as a decorative color stain for most cementitious substrates.

ADVANTAGES:

- Green Friendly
- Save to Use
- Water Based - Cleans up with Water
- Easy to Apply
- Can be Sprayed or Rolled
- Low Cost
- Wide Color Selection
- Quick Drying

SURFACE PREPARATION

Surface to which MULTI-STAIN will be applied must be completely free from all grease, oil, paint, dirt, dust, laitance, sealers, curing compounds, water repellents and other foreign materials which may interfere with bonding. Surface must be completely dry prior to MULTI-STAIN application. Concrete surfaces should be etched with acid to open pores to achieve proper effect of stain. Acid must be neutralized with soda ash, baking soda, etc., before application. When using over Multicoat's TOP COAT or KRETE KOTE, we recommend a light sanding prior to staining. Do not use acid to clean TOP COAT, KRETE KOTE, MICRO-TOPPING or STAMP MIX. Be sure surface is completely cured.

MIXING

MULTI-STAIN must be thoroughly stirred and shaken prior to use. Do not add water: use at full strength. All pails of like color stain should be combined into one container prior to use during application for uniformity.

APPLICATION

Apply MULTI-STAIN in one coat. Can be applied with a pump sprayer (recommended application), airless sprayer, by roller, sponge or broom. Apply stain generously to substrate to achieve desired color. Color will lighten slightly as it dries. Final color can be darkened by applying subsequent coats of stain: allow each coat to dry thoroughly. Then apply Multicoat's CLEARSEAL to entire area stained.



AVAILABLE IN ONE AND FIVE GALLON CONTAINERS



APPLY MULTI-STAIN WITH A PUMP SPRAYER AS SHOWN ABOVE. CAN ALSO BE SPONGED OR BROOMED.



AS SOON AS MULTI-STAIN HAS DRIED, USUALLY THE NEXT DAY, APPLY 2 COATS OF MULTICOAT'S CLEAR SEAL TO LOCK IN THE COLOR AND PROTECT THE SURFACE.



LIMITATIONS

Do not apply if substrate temperature is below 40°F or above 100°F, or if ambient temperature below 40°F above 100°F.

Do not apply if precipitation is expected within a twenty four (24) hour period.

We strongly recommend that a small test area be applied to select final color. This is a transparent stain product and will not be a solid color. There will be several variations of color throughout the project. There are factors on each job that will affect the final color outcome; workmanship, weather, surface absorption, texture of the substrate, type of substrate, etc.

COVERAGE

One coat will cover approximately 200 sq. ft. per gallon depending upon surface texture and porosity. Coverage should not be less than 200 sq. ft per gallon.

PACKAGING AND STORAGE

Packaged in 1-gallon cans, and 5-gallon pails. Store in a dry place at 60 to 85 deg F. Shelf life is approximately 18 months.

DAMAGE LIMITATION

Seller shall not be liable for any damages, injury, loss, direct or consequential, resulting from its products. The parties intend that the limitation of damages, including consequential damages, applies even if the exclusive remedy provided for herein fails of its essential purpose.

EXCLUSIVE REMEDY

Seller's sole obligation, and buyer's exclusive remedy shall be to replace material if found to be defective.

WARRANTY DISCLAIMER

There are no warranties which extend beyond the description of the fact hereof. Seller expressly disclaims all other warranties regarding the use of its products, whether expressed or implied, including the implied warranties of merchantability and for fitness of a particular purpose. Since use of the product is beyond the Seller's control, the Buyer assumes all risk of use.

WARRANTY

Materials are guaranteed with respect to uniformity and quality within manufacturer's specifications.



MULTICOAT® CORPORATION West Coast

Toll Free: (877) 685-8426
(949) 888-7100 Fax (949) 888-2555
Website: www.multicoat.com
E-mail: info@multicoat.com

MULTICOAT® PRODUCTS, INC. East Coast

Toll Free: (800) 660-6729
(304) 586-0616 Fax (304) 586-0620
Website: www.multicoat.com
E-mail: info@multicoat.com

AVAILABLE THROUGH