



Clear Gloss Solvent Sealer & Color Enhancer

SEAL BRITE - CA

DESCRIPTION AND USE:

Seal Brite—CA is a clear, VOC Compliant, solvent sealer comprised of a solution of 100% methacrylate polymers for enhancing and protecting decorative concrete, and concrete overlays. Compared to typical sealers, Seal Brite — CA provides increased protection against water intrusion and freeze/thaw cycles, chemical erosion, de-icing salts, and yellowing.

ADVANTAGES:

- Excellent Abrasion Resistance
- Single Component Packaging
- Weather and Freeze-Thaw Resistant
- Low Cost
- Enhances Color
- SCAQMD Compliant



BASIC USE:

Seal Brite is a liquid material, applied via roller, brush or spray onto masonry surfaces to act as a sealer, color enhancer and a protective layer.

COLOR / APPEARANCE:

Clear / Glossy

SURFACE PREPARTION:

Substrate must be structurally sound, free from grease, oil, paint, dirt, dust, sealers, laitance, curing compounds, and any other foreign material which may prevent proper bonding. Surface must be dry and thoroughly cured prior to application of Seal Brite—CA. Do not use if substrate is subject to negative side water, vapor pressure or any type of negative side waterproofing application.

MIXING:

Seal Brite—CA is supplied in a ready-to-use condition, but it should be stirred prior to use to eliminate any phase separation or settling which may occur upon shipping and storage. Do not thin.

APPLICATION:

Apply in a uniform manner by airless spray, brush, or roller. Maintain a wet edge to prevent lap marks. Apply in well ventilated area, away from sparks or open flames.

CURING:

Curing time will vary due to weather conditions, thickness, substrate absorption, etc. Material should be protected from water and extreme weather elements for a minimum of 24 hours.



COVERAGE:

250 to 300 square feet per gallon.

PACKAGING:

1-Gallon Cans, and 5-Gallon Pails.

LIMITATIONS:

Do not apply if precipitation is expected within twelve hours of application. Do not apply if ambient air temperature is 40° F and falling or above 100° F and rising. Do not add other materials to the mixture of the product. Do not use if substrate is subject to negative side water, vapor pressure or any type of negative side waterproofing application. It is recommended to check moisture levels (should be below 10%) before application. On areas which may become wet, it is recommended that an anti-skid material be added into the containers of Seal Brite-CA and thoroughly mixed prior to application to achieve a more non-skid surface.

STORAGE:

Store material in a dry location. Store away from direct contact with the ground or concrete. Protect from weather and other possible damage. Store between 50° F and 90° F and away from open flames. Minimum shelf life is 24 months from date of manufacture when properly stored in unopened containers.

CLEANING:

Clean tools and spills with Xylene. (Use proper safety precautions when using these types of cleaners.)

SAFETY INFORMATION:

Obtain MSDS sheet from Multicoat’s website or by calling the toll free numbers below. This product contains solvents which have associated health and fire hazards. Avoid breathing vapors and minimize contact. Wear appropriate personal protection equipment. Keep away from sparks and open flames, or any source of ignition. Dispose of empty containers in accordance with all applicable regulations. Consult this product’s MSDS for further health, safety, and regulatory information.

WARRANTY DISCLAIMER:

There are no warranties which extend beyond the description of the fact hereof. Seller expressly disclaims all other warranties regarding the use of its products, whether expressed or implied, including the implied warranties of merchantability and for fitness of a particular purpose. Since use of the product is beyond the Seller’s control, the Buyer assumes all risk of use. **EXCLUSIVE REMEDY:** Seller’s sole obligation, and buyer’s exclusive remedy shall be to replace material if found to be defective. **DAMAGE LIMITATION:** Seller shall not be liable for any damages, injury, loss, direct or consequential, resulting from its products. The parties intend that the limitation of damages, including consequential damages, applies even if the exclusive remedy provided for herein fails of its essential purpose. **FOR PROFESSIONAL USE ONLY:** Multicoat products should be used by licensed contractors. Multicoat is not a contractor and the contractor remains liable for all damages and inadequate product performance caused by construction means, methods, sequences and techniques that are used to install the product which may include: design and construction of the substrate and the selection and installation of all sealants, flashings, and related components.

TEST DATA - SEAL BRITE-CA SYSTEM

Average Dry Time at 70° F

Tack Free	20-60 Minutes
Recoat	2-4 Hours
Full Cure	Overnight

Physical Properties

Percent Solids	23-24%
Viscosity at 77° F	20-24 Seconds Zahn #2
Gloss @ 60° Angle	80 + @ 60
Desired Dry Film	1.2 to 1.3 MILS



MULTICOAT® CORPORATION

West Coast

Toll Free: (877) 685-8426
(949) 888-7100 Fax (949) 888-2555
Website: www.multicoat.com
E-mail: info@multicoat.com

MULTICOAT® PRODUCTS, INC.

East Coast

Toll Free: (800) 660-6729
(304) 586-0616 Fax (304) 586-0620
Website: www.multicoat.com
E-mail: info@multicoat.com

AVAILABLE THROUGH

The Coating of the Future... Today