



Waterproofing for New or Existing Fountains, Water Features & Ponds

WATERPROOFING KIT

DESCRIPTION & USE

Multicoat's Elastomeric Waterproofing Kit is a self-contained unit containing a liquid waterproofing membrane and a color coat along with accessory items. This kit is designed to waterproof new or existing concrete (or block) fountains, ponds, reflection pools, etc.

ADVANTAGES:

- Easy 2-Step Paint on Application
- Easy Clean Up
- Environmentally Friendly
- Multiple Color Options
- Water-based Materials - Safe to Use
- No Special Tools Required

SURFACE PREPARATION

Surface must be structurally sound and free from grease, oil, dirt, dust, sealers, water repellents and other foreign materials which may interfere with proper bonding. All cracks & holes must be filled with suitable cementitious material (such as Multicoat's Speed Mix 2000) before membrane is applied. Certain types of porous block/substrates must be parged before applying waterproofing membrane. Substrate must be completely dry to avoid gassing or bubbling of waterproof membrane. If membrane bubbles, cut the bubble out and let dry, then re-coat area. Coat complete interior to the top edge of container. New concrete must cure 20 days before applying the waterproof membrane. If this product is to be used for ponds or fountains meant to contain fish, all instructions on the reverse side must be carefully followed.

APPLICATION

STEP 1: Stir Elastomeric Waterproofing Membrane with hand paddle. Roll or brush over area to be water-proofed with one (1) coat at a coverage rate of 50 sq. ft. per gallon. Make sure not to puddle membrane in the corners. Apply COLORCOAT when the waterproofing membrane is completely dry. Do not allow the waterproofing membrane to be exposed for more than two (2) days without the COLORCOAT finish.

DO NOT MIX STEP 1 and STEP 2 TOGETHER

STEP 2: Surface to which COLORCOAT is applied must be clean and completely dry prior to COLORCOAT application. Mix COLORCOAT to uniformity with hand paddle or gently shake container. Apply COLORCOAT with 1/2" nap roller for smooth and 3/4" nap roller for rough surfaces. Make sure to cover water-proofing membrane completely. Allow the pond to sit dry 10-14 days before filling with water. If this product is to be used for ponds or fountains containing fish, all instructions on the enclosed fishpond sheet must be carefully followed.



COVERS APPROX 50 SQ. FT.



BRUSH WATERPROOFING MEMBRANE INTO ALL CORNERS.



ROLL OR BRUSH WATERPROOFING MEMBRANE ON THE REMAINING SURFACES TO BE WATERPROOFED



BRUSH COLORCOAT INTO ALL CORNERS.



ROLL OR BRUSH COLORCOAT ONTO REST OF AREA MAKING SURE TO COMPLETELY COVER WATERPROOFING MEMBRANE.



LIMITATIONS

Do not apply if substrate temperature is below 40°F or above 100°F, or if ambient temperature below 40°F above 100°F.

Do not apply if precipitation is expected within a twenty four (24) hour period.

Do not allow waterproofing membrane to become wet or to be left exposed more than 2 days in extreme UV Ray areas.

Do not use if substrate is subject to negative side water or water vapor pressure.

COVERAGE

Each Waterproofing Kit contains enough waterproofing membrane and color coat to cover approx. 50 square feet.

PACKAGING / STORAGE

Each waterproofing kit is packaged in a self-contained box containing the water proofing membrane, color coat, stir sticks, application instructions and instructions for ponds meant to hold fish.

Store boxes at 40° to 90° F. Shelf life approximately 18 months.

COLORS

Currently there are five available colors: White, Nordic Grey, Charcoal, Aqua Blue, Sundance.

DAMAGE LIMITATION

Seller shall not be liable for any damages, injury, loss, direct or consequential, resulting from its products. The parties intend that the limitation of damages, including consequential damages, applies even if the exclusive remedy provided for herein fails of its essential purpose.

EXCLUSIVE REMEDY

Seller's sole obligation, and buyer's exclusive remedy shall be to replace material if found to be defective.

WARRANTY DISCLAIMER

There are no warranties which extend beyond the description of the fact hereof. Seller expressly disclaims all other warranties regarding the use of its products, whether expressed or implied, including the implied warranties of merchantability and for fitness of a particular purpose. Since use of the product is beyond the Seller's control, the Buyer assumes all risk of use.

WARRANTY

Materials are guaranteed with respect to uniformity and quality within manufacturer's specifications.

FISHPOND SPECIAL INSTRUCTIONS

IF THIS PRODUCT IS TO BE USED FOR PONDS OR FOUNTAINS MEANT TO CONTAIN FISH ALL INSTRUCTIONS ON THIS SHEET MUST BE CAREFULLY FOLLOWED.

Since there are many application variables beyond our control we recommend the following procedures to assure that every thing is properly cured and ready to provide a healthy environment for your fish.

Apply products per label instructions and allow to cure for at least 10 days before adding water.

After 10 days fill the pond with water and do not add any fish. Allow the pond to set for five days and then drain the pond and wash down all surfaces with fresh water.

Refill the pond and allow water to stabilize over night before adding a test fish. Note: we always recommend adding a test fish (We suggest using feeder goldfish available from most fish or pet stores.) to assure that the water is fish safe before adding more expensive decorative fish.

If the test fish is still alive after 3 days then go to the next step; if the fish does not survive, drain the pond and wash down all surfaces with fresh water. Refill the pond and allow water to stabilize over night before adding another test fish.

Once the pond has proven safe for the feeder fish then the next step depends on whether the decorative fish are new or being transferred from an existing pond. *Consult your fish provider/supplier for specific directions on transferring your fish to your refurbished pond.*



MULTICOAT® CORPORATION
West Coast

Toll Free: (877) 685-8426
(949) 888-7100 Fax (949) 888-2555
Website: www.multicoat.com
E-mail: info@multicoat.com

MULTICOAT® PRODUCTS, INC.
East Coast

Toll Free: (800) 660-6729
(304) 586-0616 Fax (304) 586-0620
Website: www.multicoat.com
E-mail: info@multicoat.com

AVAILABLE THROUGH

MC311

The Coating of the Future... Today