

MATERIAL SAFETY DATA SHEET

Manufacture's Name:

Date of Preparation:

November 24 ,2004

Information Telephone No:
949-888-7100



MULTICOAT CORPORATION
23331 ANTONIO PARKWAY
RANCHO SANTA MARGARITA, CA 92688

SECTION I – PRODUCT IDENTIFICATION

Chemical name:
MULTI-TEX STUCCO MIX

SECTION II – HAZARDOUS INGREDIENTS

May contain the following:

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>EXPOSURE LIMITS IN AIR (Give Units)</u>			
		<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>	
Ammonia	7664-41-7		25 ppm		50 ppm
Propylene Glycol	57-55-6		NE		
Preservative	4080-31-3		NE		
Coalescent	25265-77-4		NE		

SECTION III – PHYSICAL DATA

<u>Melting Point/Freezing Point:</u> 0°C/32°F (Water)	<u>Boiling Point:</u> 100°C/212°F (Water)	<u>Specific Gravity (Water = 1):</u> 1.6 to 1.8.
<u>Evaporation Rate (Butyl Acetate = 1):</u> Less than 1 (Water)	<u>Solubility in Water:</u> Dilutable Aqueous Dispersion	<u>Vapor Pressure:</u> 7mm Hg @ 20°C/68°F

Appearance and Odor:

White or colored plaster, mild ammoniacal or acrylic odor.

VOC Content < 100 grams per liter

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Flash point: Not Applicable

Auto Ignition Temperature: Not applicable

Extinguishing Media: Material is not combustible
Use Water.

Splatter:

The wet dispersion will splatter above 100°C/212°F (Boiling point of water).

Special Firefighting Procedures:

Firefighters should be equipped with self-contained breathing apparatus and full protective gear.

SECTION V – HEALTH HAZARD DATA

ROUTE(S) OF ENTRY:

Inhalation – Vapor or mist can cause headaches, nausea, and irritation of the nose, throat and lungs.

Skin Contact – May be irritating upon repeated or prolonged contact. Wash skin with soap and water after contact.

Eye Contact – Flush eyes with large amount of water for at least 15 minutes. Consult physician if irritation persists.

HAZARD RATING (NFPA 704)

HEALTH EFFECTS

The effects of over-exposure are based on acute toxicity profiles for a number of acrylic emulsions that are compositionally similar to the binder used in this product.

Typical values are:	Rate, oral LD50:	>5.0 g/kg
	Rabbit, dermal LD50	>5.0 g/kg
	Rabbit	Eye irritation

Acute effects: Non-toxic by ingestion. May cause eye and skin irritation

Chronic effect: No known chronic health effects

FIRST AID/EMERGENCY PROCEDURES

Eye Contact:

Flush eyes immediately with running water for 15 minutes, including under eyelids. Consult a physician if irritation persists.

Skin Contact:

Wash with soap & water.

Inhalation:

Move subject to fresh air. If breathing is difficult consult a physician.

Ingestion:

Dilute with large amounts of water and consult physician.

SUSPECTED CANCER AGENT?

NO This product's ingredients are not found in the Federal OSHA, NTP, IARC

California employers using CAL-OSHA – regulated carcinogens must register with CAL-OSHA. CAL-OSHA and Federal OSHA carcinogen lists are similar.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None other than the above listed.

SECTION VI – REACTIVITY DATA

Stability: Stable.

Incompatibility: None

Hazardous Polymerization: Will not occur.

Conditions to Avoid: None known

SECTION VII – SPILL, LEAK AND DISPOSAL PROCEDURES

Spill response procedures (Include employee protection measures):

Normal clean up precautions of Section VII.

Preparing wastes for disposal (container types, neutralization, etc.):

May be salvaged for use or removed to a landfill dump in accordance with regulations.

SECTION VIII – SPECIAL PROTECTION INFORMATION

Ventilation and engineering controls:

Provide general ventilation and local exhaust ventilation to remove vapor or mist in confined spaces.

Respiratory Protection (type):

NIOSH approved respirator.

Eye Protection (type):

Approved tight-fitting safety goggles or glasses.

Glover (specify material):

Gloves/Rubber.

Other clothing and equipment:

Clean, body-covering protective clothing, such as long-sleeve shirt with buttoned collar, long pants extending over tops of work shoes.

Work practices, hygienic practices: Keep work area clean to avoid creating excessive dust.

STORAGE & HANDLING:

Storage temperature: Maximum 30°C/85°F
 Minimum 4°C/40°F

KEEP FROM FREEZING – PRODUCT WILL COAGULATE

Protective measures of contaminated equipment: None other than listed above.

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Multicoat Corporation assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.